


X VANE / SQUARE SPRAY PATTERN / THREE-PIECE DESIGN / EASY CLEAN

BB/BD series full cone nozzles offer a three-piece design made of body, X-vane and connection. BB/ BD series nozzles supply a square section spray pattern and are suitable for working environments that strictly require a uniform coverage. The most important feature of BB/BD series nozzle is their X-vane which can be easily disassembled. It is mounted between its body and connection, allowing the narrowest passage to avoid clogging. The best choice to solve clogging problems.

■ Thread specification Male (BSPT, NPT) Female (BSP, NPT)








SQUARE SPRAY

BBQ Female	BDQ Male	Code	RF RG	D	D1	Capacity (I/min) at different pressure values (bar)				Spray angle (°) at pressure (bar)					
			inch	mm	mm	0.7	1.0	2.0	3.0	5.0	7.0	10	0.5	1.5	6.0
•	•	1270	1/8"	1.8	1.0	1.30	1.56	2.21	2.70	3.49	4.12	4.93	40°	52°	47°
•	•	1360	1/0	1.9	1.3	1.74	2.08	2.94	3.60	4.65	5.50	6.57	48°	63°	57°
•	•	1440		2.1	1.3	2.13	2.54	3.59	4.40	5.68	6.72	8.03	60°	66°	60°
•	•	1740	1/4"	2.8	1.6	3.58	4.27	6.04	7.40	9.55	11.3	13.5	62°	67°	61°
•	•	1890		3.2	1.6	4.30	5.14	7.27	8.90	11.5	13.6	16.3	70°	75°	68°
•	•	2110		3.8	1.6	5.31	6.35	8.98	11.0	14.2	16.8	20.1	78°	82°	75°
•	•	2133	3/8"	3.8	2.4	6.42	7.68	10.9	13.3	17.2	20.3	24.3	71°	75°	68°
•	•	2210	1/2"	5.6	3.0	10.1	12.1	17.2	21.0	27.1	32.1	38.3	71°	75°	68°
•	•	2270		6.4	3.2	13.0	15.6	22.1	27.0	34.9	41.2	49.3	78°	82°	75°

BB/ BD series nozzles produce a square spray pattern. The flat spray orientation is set with a 10°-15° offset angle from the main manifold axis to avoid jet overlapping. Therefore the correct alignment of these nozzles is very important and must be done properly. Please refer to the table below.







DIMENSIONS AND WEIGHTS

Nozzle type	RF inch	H mm	WS mm	W kg
	1/8"	30	14	0.03
BB	1/4"	37	17	0.04
Female	3/8"	46	19	0.07
	1/2"	57	25	0.20

Nozzle type	RG inch	H mm	WS mm	W kg				
	1/8"	32	14	0.02				
BD	1/4"	39	17	0.04				
Male	3/8"	47	19	0.07				
	1/2"	57	25	0.20				

Typical applications

Washing: exhaust scrubbers, parts cleaning, pre-treatment for coating processes

Cooling: exhaust gas cooling, tank cooling Coating: oil coating, spray of chemicals Other applications: dust control, leak test





MATERIAL • B1 - AISI 303 Stainless steel

• B31 - AISI 316L Stainless steel

o T1 - Brass (optional)

